PURPOSE:

This specification outlines the Quality System requirements for Young & Franklin/Tactair Fluid Controls suppliers. It is intended to assure that articles purchased from approved suppliers are as ordered and have been subjected to positive control during the supplier s handling and storage.

GENERAL:

The supplier s Quality System *shall* be documented in the form of a Quality Manual, supported by documented procedures as necessary. These documents *shall* be available for review by Young & Franklin/Tactair Fluid Controls.

Young & Franklin/Tactair Fluid Controls approval of the supplier s Quality System is limited to the location shown on Young & Franklin/Tactair Fluid Controls Purchase Order and is not transferable to the supplier s other stocking locations or affiliated companies.

YFTFC004 QUALITY SYSTEM REQUIREMENTS

1.0 MANAGEMENT RESPONSIBILITY

Management *shall* immediately notify Young & Franklin/Tactair Fluid Controls of any significant changes in the Quality Program, leadership, procedures, or processes which would affect the quality of products.

1.1 Quality Policy

The supplier *shall* define and document its quality policy. The quality policy *shall* be relevant to the supplier organizational goals and the expectations and needs of its customers. The supplier *shall* ensure that this policy is understood, implemented, and maintained at all levels of the organization.

1.2 Responsibility and Authority

The supplier's personnel performing quality functions *shall* have sufficient, well-defined responsibility, authority, and the organizational freedom to identify and evaluate quality problems, and to initiate, recommend, or provide solutions.

1.3 M anagement Review

Management *shall* periodically review the status and adequacy of the quality system to ensure its continuing effectiveness in satisfying the supplier s stated quality policy and objectives. Records of such reviews *shall* be maintained.

2.0 QUALITY SYSTEM

2.1 General

The supplier *shall* establish, document, implement, and maintain a quality system to assure product compliance to specified requirements.

The supplier *shall* maintain a quality manual that includes or makes reference to quality system procedures and outline the structure of the documentation used in the quality system.

3.0 CONTRACT REVIEW

3.1 Review

The supplier s quality function *shall* assure the supplier s procurement documents incorporate applicable quality, and technical requirements, and verifies that items are procured from approved sources when required by Young & Franklin/Tactair Fluid Controls Purchase Order.

3.2 Amendment to Contract

The supplier *shall* identify how an amendment to a contract is made and correctly transferred to the functions concerned within the supplier s organization.

3.3 Records

Records of contract reviews *shall* be maintained.

4.0 DOCUMENT AND DATA CONTROL

4.1 General

The supplier *shall* establish and maintain documented procedures to control all documents and data that relate to the requirements of this standard including to the extent applicable, documents of external origin such as standards and customer drawings. In essence a system is maintained to control the initiation, revision, issue, and distribution of all Quality related documents.

5.0 PURCHASING

5.1 General

The supplier *shall* establish and maintain documented procedures to ensure that purchased product conforms to specified requirements.

6.0 PRODUCT IDENTIFICATION AND TRACEABILITY

The supplier *shall* establish and maintain documented procedures for identifying product by suitable means from receipt and during all stages of production, delivery, and installation.

The supplier *shall* establish and maintain documented procedures for unique identification of individual product or batches. This identification *shall* be recorded.

7.0 PROCESS CONTROL

The Supplier *shall* identify and plan the production, installation, and servicing processes which directly affect quality and *shall* ensure that these processes are carried out under controlled conditions.

Controlled conditions *shall* include the following:

Documented procedures defining the manner of production, installation, and servicing, where the absence of such procedures could adversely affect quality;

Use of suitable production, installation, and servicing equipment, and a suitable working environment;

Compliance with reference standards/codes, quality plans, and/or documented procedures;

Monitoring and control of suitable process parameters and product characteristics;

Approval of processes, equipment and personnel as appropriate;

Criteria for workmanship, which *shall* be stipulated in the clearest practical manner (e.g., written standards, representative samples, or illustrations);

Suitable maintenance of equipment to ensure continuing process capability.

Where the results of processes cannot be fully verified by subsequent inspection and testing of the product and where, for example, processing deficiencies may become apparent only after the product is in use, the processes *shall* be carried out by qualified operators and/or *shall* require continuous monitoring and control of process parameters to ensure that the specified requirements are met.

The requirements for any qualification of process operations, including associated equipment and personnel *shall* be specified.

Records shall be maintained for qualified processes, equipment, and personnel, as appropriate.

8.0 INSPECTION AND TESTING

The supplier shall establish and maintain documented procedures for inspection and testing activities to

verify the specified requirements for the product are met.

The required inspection, testing with records *shall* be established and detailed in the quality plan or a documented procedure.

8.1 Receiving Inspection and Testing

The supplier *shall* ensure that incoming product is not used or processed until it has been inspected or otherwise verified as conforming to specified requirements. Verification of the specified requirements *shall* be in accordance with the quality plan and/or documented procedures.

8.2 In-process Inspection and Testing

The supplier shall:

Inspect and test the product as required by the quality plan and/or documented procedures; Hold product until the required inspection and tests have been completed or necessary reports have been received and verified, except when product is released under positive-recall procedures *shall* not preclude the activities.

8.3 Final Inspection and Testing

The supplier *shall* carry out all final inspection and testing in accordance with the quality plan and/or documented procedures to complete the evidence of conformance of the finished product to the specified requirements.

8.4 Inspection and Test Records

The supplier *shall* establish and maintain records which provide evidence that the product has been inspected and/or tested. These records *shall* show clearly whether the product has passed or failed the inspections and/or tests according to defined acceptance criteria. Where the product fails to pass any inspection and/or test, the procedures for control of non-conforming product *shall* apply.

Records *shall* identify the inspection authority responsible for the release of product.

9.0 CONTROL OF INSPECTION, MEASURING, AND TEST EQUIPMENT

Control and calibration of instrumentation and calibration standards shall be in accordance with the requirements of ISO-10012-1 and ANSI/ASQ Z 540-1. The supplier *shall* establish and maintain documented procedures to control, calibrate, and maintain inspection, measuring, and test equipment (including test software) used by the supplier to demonstrate the conformance of product to the specified requirements. Inspection, measuring, and test equipment *shall* be used in a manner which ensures that the measurement uncertainty is known and is consistent with the required measurement capability.

Where test software or comparative references such as test hardware are used as suitable forms of inspection, they *shall* be checked to prove that they are capable of verifying the acceptability of product, prior to release for use during production, installation, or servicing, and *shall* be rechecked at prescribed intervals. The supplier *shall* establish the extent and frequency of such checks and *shall* maintain records as evidence of control.

Where the availability of technical data pertaining to the measurement equipment is a specified requirement, such data *shall* be made available, when required by the customer or customer s representative, for verification that the measuring equipment is functionally adequate.

9.1 Control Procedure

The supplier *shall*:

Determine the measurements to be made and the accuracy required, and select the appropriate inspection, measuring and test equipment that is capable of the necessary accuracy and precision;

Identify all inspection, measuring, and test equipment that can affect product quality, and calibrate and adjust them at prescribed intervals, or prior to use, against certified equipment having a known valid relationship to internationally or nationally recognized standards. Where no such standards exist, the basis used for calibration *shall* be documented;

Define the process employed for the calibration of inspection, measuring, and test equipment, including details of equipment type, unique identification, location, frequency of checks, check method, acceptance criteria, and the action to be taken when results are unsatisfactory; Identify inspection, measuring, and test equipment with a suitable indicator or approved identification record to show the calibration status;

Maintain calibration records for inspection, measuring, and test equipment

Assess and document the validity of previous inspection and test results when inspection, measuring and test equipment is found to be out of calibration;

Ensure that the environmental conditions are suitable for the calibrations, inspections, measurements, and tests being carried out;

Ensure that the handling, preservation, and storage of inspection, measuring, and test equipment is such that the accuracy and fitness for use are maintained;

Safeguard inspection, measuring, and test facilities, including both test hardware and test software, from adjustments which would invalidate the calibration setting.

10.0 INSPECTION AND TEST STATUS

The inspection and test status of product *shall* be identified by suitable means, which indicate the conformance or non-conformance of product with regard to inspection and tests performed. The identification of inspection and test status *shall* be maintained, as defined in the quality plan and/or documented procedures, throughout production, installation, and servicing of the product to ensure that

only product that has passed the required inspections and tests or released under an authorized concession is dispatched, used, or installed.

11.0 CONTROL OF NONCONFORMING PRODUCT

The supplier *shall* establish and maintain documented procedures to ensure that product that does not conform to specified requirements is prevented from unintended use or installation. This control *shall* provide for identification, documentation, evaluation, segregation (when practical), disposition of non-conforming product, and for notification to the functions concerned.

11.1 Review and Disposition of Nonconforming product

The responsibility for review and authority for the disposition of non-conforming product *shall* be defined.

Non-conforming product *shall* be reviewed in accordance with documented procedures.

Reworked to meet the specified requirements, Accepted with or without repair by concession (must be approved by the customer) Rejected or scrapped.

Where required by the contract, the proposed use or repair of product which does not conform to specified requirements *shall* be reported for concession to the customer or customer s representative. The description of the non-conformity that has been accepted, and of repairs, *shall* be recorded to denote the actual condition.

Repaired and/or reworked product *shall* be reinspected in accordance with the quality plan and/or documented procedures.

12.0 CORRECTIVE AND PREVENTIVE ACTION

12.1 General

The supplier *shall* establish and maintain documented procedures for implementing corrective and preventive action.

Any corrective or preventive action taken to eliminate the causes of actual or potential non-conformities *shall* be to a degree appropriate to the magnitude of problems and commensurate with the risks encountered.

The supplier *shall* implement and record any changes to the documented procedures resulting from

corrective and preventive action

12.2 Responding to Corrective Action Requests.

The supplier *shall* respond to a corrective action request in a timely manner. A letter sent to the supplier from Young & Franklin/Tactair Fluid Controls gives a description of non-conformities along with a due date that the supplier *shall* respond by. When suppliers do not respond to the corrective action by the due date, their approved supplier status may be revoked and payment for products may be withheld.

13.0 HANDLING, STORAGE, PACKAGING, PRESERVATION, AND DELIVERY

The supplier shall establish and maintain documented procedures for handling, storage, packaging, preservation, and delivery of product.

13.1 Handling

The supplier *shall* provide methods of handling product that prevent damage or deterioration.

13.2 Storage

The supplier *shall* use designated storage areas or stock rooms to prevent damage or deterioration of product, pending use or deliver. Appropriate methods for authorizing receipt to and dispatch from such areas *shall* be stipulated. In order to detect deterioration, the condition of product in stock *shall* be assessed at appropriate intervals.

13.3 Packaging

The supplier *shall* control packing packaging, and marking processes (including materials used) to the extent necessary to ensure conformance to specified requirements.

13.4 Preservation

The supplier *shall* apply appropriate methods for preservation and segregation of product when the product is under the supplier s control.

13.5 Delivery

The supplier *shall* arrange for the protection of the quality of product after final inspection and test. Where contractually specified, this protection *shall* be extended to include delivery to destination.

14.0 CONTROL OF QUALITY RECORDS

The supplier *shall* establish and maintain documented procedures for identification, collection, indexing, access, filing, storage, maintenance, and disposition of quality records.

The supplier *shall* maintain adequate records of all inspections and tests. The records *shall* indicate

the nature and number of observations made, the number and type of deficiencies found, the quantities approved and rejected and the nature of corrective action taken as appropriate.

Such records *shall* be made available to Young & Franklin/Tactair Fluid Controls upon request; and *shall* be retained for eight years after final payment under the related PO or for an additional period as imposed in the Purchase Order.

All quality records *shall* be legible and *shall* be stored and retained in such a way that they are readily retrievable in facilities that provide a suitable environment to prevent damage or deterioration and to prevent loss.

Records may be in the form of any type of media, such as hard copy or electronic media.

15.0 TRAINING

The supplier *shall* establish and maintain documented procedures for identifying training needs and provide for the training of all personnel performing activities affecting quality. Personnel performing specific assigned tasks *shall* be qualified on the basis of appropriate education, training and/or experience, as required. Appropriate records of training *shall* be maintained.

Training certification or qualification of individuals performing processes ie: X-ray, fluorescent penetrant, welding, magnetic particle, ultrasonic inspection shall be documented. Any approval where the Level III individual does not possess a current Professional Level III Certification *shall* use the words Internal Support Only on that approval.

For Non-Destructive Inspection (NDT) Level III inspectors or any Level III acting as a consultant for multiple processors must have a current Professional Level III Certification.

16.0 STATISTICAL TECHNIQUES

The supplier *shall* maintain the ability to perform SPC when required by Young & Franklin/Tactair Purchase Order.